







	DT-R17L4D	DT-V17G1Z	DT-R24L4D	DT-V24G1Z	DT-V20L3GZ	DT-V9L3DY
	 \$2,395	 \$3,300	 \$3,995	 \$4,995	 \$3,795	 \$2,495
Viewable Screen size (diag.)	17-inch	17-inch	24-inch	24-inch	20-inch	9-inch
Screen type	Active matrix LCD (IPS)	Active matrix LCD (IPS)	Active matrix LCD (IPS)	Active matrix LCD (IPS)	Active matrix LCD (IPS)	Active matrix LCD
Aspect ratio	16:9	16:9	16:10	16:10	16:10	15:9
Viewing angle (H/V)	178° / 178°	178° / 178°	178° / 178°	178° / 178°	178° / 178°	170° / 170°
Pixels	1366 x 768	1366 x 768	1920 x 1200	1920 x 1200	1680 x 1050	800 x 480
Brightness / Contrast	350cd / 900:1	350cd / 900:1	400cd / 1000:1	400cd / 1000:1	470cd / 700:1	350cd / 400:1
Waveform monitor	No	Yes	No	Yes	Yes	Yes
Vectorscope	No	Yes	No	Yes	Yes	No
Closed captioning	None	Analog/Digital ITU 608/708	None	Analog/Digital ITU 608/708	Analog/Digital ITU 608/708	Analog
Image processing	1080p 10-bit 4:4:4	1080p 10-bit 4:4:4	1080p 10-bit 4:4:4	1080p 10-bit 4:4:4	1080p 10-bit 4:4:4	4:2:2 8-bit
Chroma range	100% EBU	100% EBU	100% EBU	100% EBU	Standard	Standard
1:1 Monitoring mode	Yes	Yes	Yes	Yes	Yes	No
On screen audio metering	Digital (up to 12 ch)	Digital (up to 12 ch)	Digital (up to 12 ch)	Digital (up to 12 ch)	Digital (up to 12 ch)	Digital (up to 12 ch)
On screen time code	Yes	Yes	Yes	Yes	Yes	Yes
SD/HDSDI inputs	x2 in, 1 switched out with embedded audio/TC	x2 in, 1 switched out with embedded audio/TC	x2 in, 1 switched out with embedded audio/TC	x2 in, 1 switched out with embedded audio/TC	x2 in, 1 switched out with embedded audio/TC	x2 in, 1 switched out with embedded audio/TC
Dual link / 3G	No	Yes	No	Yes	Yes	No
DVI Input	Yes	Yes	Yes	Yes	Yes	No
Component input/output	No	Yes (Y, Pb, Pr)	No	Yes (Y, Pb, Pr)	Yes (Y, Pb, Pr)	Yes (Y, Pb, Pr)
Composite video in/out	x1	x1	x2	x2	x2	x1 (connector shared w/component)
External sync	No	No	No	Yes	Yes	No
Audio speaker	Yes	Yes	Yes	Yes	Yes	Yes
Analog audio input	L/R (x1)	L/R (x1)	L/R (x2)	L/R (x2)	L/R (x2)	mono (x1)
Analog audio monitor	L/R (x1)	L/R (x1)	L/R (x1)	L/R (x1)	L/R (x1)	mono (x2)
Remote control	MAKE/Trigger RS-485 (I/O) RS-232C	MAKE/Trigger RS-485 (I/O) RS-232C	MAKE/Trigger RS-485 (I/O) RS-232C	MAKE/Trigger RS-485 (I/O) RS-232C	MAKE/Trigger RS-485 (I/O) RS-232C	MAKE/Trigger
Power requirement	AC 120/220V, 50-60Hz	AC 120/220V, 50-60Hz DC 12-17V	AC 120/220V, 50-60Hz	AC 120/220V, 50-60Hz	AC 120/220V, 50-60Hz	AC 120/220-240 V, 50/60 Hz DC 12-17 V
Carry handle	No	Yes	No	No	No	Yes
Desktop stand	Yes	Yes	Yes	Yes	Yes	Yes
External Monitor calibration software	Yes	Yes	Yes	Yes	Yes	No